

# **elma unimix**

## **WATERFREE READY-FOR-USE LUBRICATION SOLUTION FOR VIBRATION CLEANING PROCEDURE**

### **Description**

*elma unimix* is a waterfree solution for lubrication of complete watches after the cleaning and a singular rinsing process, e.g. by vibration. *elma unimix* is also suitable as relubricating rinsing solution after the cleaning and drying of metal precision parts.

### **Application and dosage**

Ready-for-use relubrication solution after the final rinsing process. Shake well before use!

After the cleaning of the watch work with *elma cleaning solution wf* and the subsequent rinsing with *elma suprol special*, the complete watch work is relubricated with *elma unimix* in the third bath. If no relubrication is required, use *elma suprol special* for the second rinsing bath also.

### **Hotline for application consulting**

Working days: Tel. ++49 (0) 7731 882-287. Email: [chemlab@elma-germany.com](mailto:chemlab@elma-germany.com)

### **Safety recommendations**

*elma unimix* is classified as Flammable, Harmful, and Dangerous for the environment (Xn, N, R10-51/53-65) according to the German regulations on dangerous substances / EC directives. Observe the hints indicated in the Safety Data Sheets. Always handle chemicals with care.

### **Physical-chemical characterisation**

Density: 0,78 g/ml, flash point: 23-25°C. The product is not miscible with water and keeps on top of water. Mixture of solvents free of halogens like chlorine or fluorine with small additions of different oils.

### **Disposal**

1. Disposal regulations same as for used oil / diesel / benzine.
2. Dispose via specialised disposal companies:  
European waste code: 14 06 03\*, „other solvents and solvent mixtures“.
3. Burn in suitable equipments, but according to official regulations.

Transport in appropriate suitable containers.

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. Do not discharge product unmonitored into the environment.

### **Volumes, storage and transport**

Available volumes: 1l, 2.5l and 10l.

Keep in tightly closed original container at a dry, cool and ventilated place and protected from heat and direct solar radiation. Do not store together with oxidizing agents. Do not mix with other chemicals. Keep away from ignition sources.

Shelf life: 3 years from date of production (see stamp on label).

Classification for all means of transport: class 3, UN 3295.

**Elma Hans Schmidbauer GmbH&Co KG**

Kolpingstr. 1-7, D-78224 Singen

e-mail: [info@elma-germany.com](mailto:info@elma-germany.com)

Tel.: ++49 (0) 7731 882-0

Fax: ++49 (0) 7731 882-266

[www.elma-germany.com](http://www.elma-germany.com)

23.06.2008 / P:\Produkte\PRODInfo\Produkte\englisch\word\_GB\p\_unimix\_GB.doc

