

elma clean 260 dip&splash (EC 260 d&s)

Description

elma clean 260 dip&splash (EC 260 d&s) is a neutral, foam-inhibited cleaning concentrate for hard surfaces made of metall, aluminium, light metal alloys, glas, ceramic, mineral surfaces and plastics.

Removes gentle aqueous cooling emulsions from mechanical treatments, greases and oils, fingerprints and dust as well as deposited lime soaps and prevents their redeposition.

Check magnesium alloys before application.

Application and Dosage

- Ultrasonic bath: Dosage: ~2 vol-% using tap, reosmotic or deionised water • Temperature: 30-75 °C.
- Spray cleaning: Dosage: ~1 vol-%, using tap, reosmotic or deionised water • Temperature: well above 55°C only.
- Above 40°C the prepared cleaning solution becomes opaque with increasing temperature, this does not influence on the cleaning performance.

Safety Recommendations

elma clean 260 dip&splash (EC 260 d&s) is classified as hazardous according to the Regulation (EC) No 1272/2008 [GHS] (eye irritation).

Observe also with respect to this the hints indicated in the safety data sheet and always handle chemicals with care.

Physical-chemical characterisation

- Density: 1.059 g/ml • pH (concentrate): ~7.1.
- Ingredients according to Annex VII, A, Regulation (EC) No 648/2004 on detergents:
5-15 % anionic surfactants, 5-15 % non-ionic surfactants, <5 % phosphates, < 5 % polycarboxylates.

Disposal

The surfactants in our product meet the criteria for biodegradation as laid down in Annex III of the Regulation (EC) No 648/2004 on detergents.

The used cleaning solution can be fed into the public sewage system; observe the local pH limit values and make sure that the contamination contained in the used cleaning solution complies with the local sewage regulations.

European waste code: 20 01 30, „detergents other than those mentioned in 20 01 29“.

Volumes, Storage and Transport

- Available volumes: 2.5 l HDPE-can [REF](#) 8000072, 5 l HDPE-can [REF](#) 8000030, 10 l HDPE-can [REF](#) 8000073, 25 l HDPE-can [REF](#) 8000029 and 200 l barrel [REF](#) 8000028.
- Store in closed original container at a temperature between +5 °C and 30 °C, protected from heat and direct solar radiation. After eventual storage below 5 °C a) shake thoroughly or b) leave the bottles or cans for 24 h at room temperature before application.
- Shelf life: 3 years from date of production (see lot on label).
- Classification for all means of transport: no hazardous material.

Accessories

- Tap (outlet tap): for 5 / 10 l cans [REF](#) 8000003927 • for 25 l can [REF](#) 8000003928.
- Dosing cup: 250 ml vol./5 ml-scale [REF](#) 8000643 • 1000 ml vol./10 ml-scale [REF](#) 8000647.